



Solid Ramps



Solid Ramps from AmeriGlide are an excellent way to provide long term access for mobility scooter or wheelchair users. Although an AmeriGlide solid ramp can support up to 600 pounds, it is also lightweight due to its aluminum construction.

- 600 pound capacity
- 3-year transferable warranty
- Lightweight
- High traction surface
- Slotted for drainage
- Aluminum construction
- Side rails prevent slips
- Mounting hardware included
- Available in 18", 2', 3', 4', and 5' lengths





Solid Ramps

° = degree of slope
% = percent grade

				15.5° (28%)	16 in. (41 cm)
			17° (30%)	13.5° (24%)	14 in. (36 cm)
			14.5° (26%)	11.5° (27%)	12 in. (30 cm)
		16.1° (29%)	12° (21%)	9.6° (23%)	10 in. (25 cm)
		14.5° (26%)	10.8° (19%)	8.6° (20%)	9 in. (23 cm)
		12° (29%)	9.6° (17%)	7.7° (16%)	8 in. (20 cm)
	17° (30%)	11.2° (27%)	8.4° (15%)	6.7° (16%)	7 in. (18 cm)
	14.5° (26%)	9.6° (23%)	7.2° (13%)	5.7° (14%)	6 in. (15 cm)
16.1° (29%)	12° (21%)	8° (14%)	6° (10%)	4.8° (12%)	5 in. (13 cm)
12.8° (23%)	9.6° (17%)	6.4° (11%)	4.8° (8%)	3.8° (11%)	4 in. (10 cm)
9.6° (17%)	7.2° (13%)	4.8° (8%)	3.6° (6%)	2.9° (9%)	3 in. (8 cm)
6.4° (11%)	4.8° (8%)	3.2° (6%)	2.4° (4%)	1.9° (7%)	2 in. (5 cm)
3.2° (6%)	—	—	—	—	1 in. (2.5 cm)
1.5 ft. (46 cm)	2 ft. (61 cm)	3 ft. (91 cm)	4 ft. (122 cm)	5 ft. (152 cm)	

Ramp Length (feet/cm)

- Incline chart for reference only
- Refer to mobility product's owner manual for product's recommended maximum incline
- For permanent ramp installations, please refer to ADA guidelines for maximum incline

